

# TFFN

Vynylon® PVC/Nylon



Fixture, machine  
tool, or appliance  
wiring material

90°C insulation

600 volts

## APPLICATIONS

For use in fixture wire, machine tool wire, or as appliance wiring material as specified in the National Electrical Code®. When used as TFFN it may be used at temperatures not to exceed 90°C in dry locations. When used as MTW it may be used at temperatures not to exceed 60°C in wet locations or when exposed to oil or coolant. May be used at temperatures up to 90°C in dry locations (ampacity limited to that of a 75°C conductor temperature per NFPA 79). When used as AWM, conductor temperatures are not to exceed 105°C in dry locations. Gasoline and oil-resistant II for flexing service.

## CONDUCTORS

Uncoated soft copper per ASTM-B3 and ASTM-B174

## INSULATION

Color-coded, heat and moisture resistant PVC (polyvinyl chloride)

## JACKET

Clear nylon (polyamide)

## INDUSTRY STANDARDS\*

UL 66 – Fixture Wire, File No. E113087  
UL 1063 – Machine Tool Wire, File No. E85964  
ASTM-B3  
ASTM-B174  
NFPA70: National Electrical Code®  
RoHS Compliant

Cerro Wire LLC self certifies that these products satisfy the product safety requirements identified by the European Low Voltage Directive 2006/95/EC.

## SURFACE PRINT

Sample: CERROWIRE VINYLON-A 18 AWG Flexing (UL) TFFN OR MTW OR AWM GR2 600V



MADE IN THE USA

©2012, Cerro Wire LLC  
All Rights Reserved

\*It is the sole responsibility of the end user to determine suitability of this product for its intended end use and application.

**cerrowire**

Electrical Distribution Division: 800.523.3869 | FAX 877.877.9563  
www.cerrowire.com

A Marmon Group/  
Berkshire Hathaway Company

**TFFN**

Vinyon® PVC/Nylon

Product Code Number	Conductors		Covering		Approx. O.D. Inches	Allowable Ampacities*		Approx. Net Wt. Lbs./M Ft.
	AWG Size	No. of Strands	PVC Ins. Mils.	Nylon Jkt. Mils.		TFFN *	MTW **	
113-10xxx	18	16	15	4	0.088	6	7	8
113-12xxx	16	26	15	4	0.098	8	10	11

Color add code (See 1<sup>st</sup> chart below)

Package add code (See 2<sup>nd</sup> chart below)

\* TFFN Per Table 402.5 OF NFPA70, NEC® 2011 edition

\*\* MTW Per NFPA79

Colors Available (Product Code 6 <sup>th</sup> and 7 <sup>th</sup> Digits)											
AWG Size	Black 01	White 02	Red 03	Blue 04	Green 05	Orange 06	Yellow 07	Brown 08	Purple 09	Gray 10	Pink 11
18 Stranded	X	X	X	X	X	X	X	X	X	X	X
16 Stranded	X	X	X	X	X	X	X	X	X	X	X

Package Code (8 <sup>th</sup> Digit)	J	M
AWG Size	500' Spool/ 2,000' CTN.	2,500' Reel
18 Stranded	X	X
16 Stranded	X	X